

FP3813 O-band Package

High Power DFB



Product Brief

FEATURES

- Single-frequency distributed feedback (DFB) laser chip

APPLICATIONS

- Optical Fiber Communications
- RF Photonic Links
- Fiber Optic Testing
- Medical
- Sensing

Notes

1. Non-condensing
2. Measured at specified operating power.
3. Measured using our Whisperdrive laser mount
4. Above 1 GHz

OVERVIEW

The FP3813 1310 nm High Power Distributed Feedback (DFB) Laser is a high performance single spectral mode device, with maximum output power of 90 mW. The package can be operated at higher temperatures for reduced power consumption in warm ambient environments. The hermetically sealed package incorporates a two-stage internal isolator. The single mode output is in polarization maintaining fiber.

SPECIFICATIONS

General Parameter	Value	Unit
Output Power in Fiber with TEC at 25C	>90	mW
Output Power in Fiber with TEC at 85C	>42	mW
Operating Current	<550	mA
Center Wavelength	1290-1330	nm
Case Temperature Operating Range ¹	10 - 85	°C
Case Temperature Storage Range ¹	-10 - 85	°C
SMSR ²	>45	dB
Linewidth ^{2,3}	<300	kHz
RIN ^{2,4}	-150	dBc/Hz

